



## HIP SERIES P0.937 INDOOR LED DISPLAY

Perfect for any corporate environment where space is a premium, the HIP series 16:9 LED wall delivers seamless panel integration and ultra-high brightness. Give your staff and clients the most memorable visual LED experience.

### Highlights



#### High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



#### Brightness nits

With an average 500 nits and 1,000 nits maximum brightness, the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



#### Low brightness & High gray level

LED display could reveal more details, including layers and colors, than traditional displays do.



#### 160° High viewing angle

The extra wide 160° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



#### High color calibration

LED display correction technology could uniformly lighten several hundred thousand LED lights, presenting a uniform display effect with the same brightness and color scale.



#### Self-Heat Dissipation Management

Self-heat dissipation design, energy saving and noise reduction improve the service life.



## Specifications

### HIP Series

|                               |                         |
|-------------------------------|-------------------------|
| Pixel Pitch                   | P0.937                  |
| LED Type                      | 4in1 1616               |
| Thickness                     | 40mm                    |
| Module Size (W H/mm)          | 150 x 337.5             |
| Cabinet Dimension (W H/mm)    | 600 x 337.5             |
| Cabinet Resolution            | 640x360                 |
| Cabinet Weight (kg/panel)     | ≤6.5kg                  |
| Brightness (Nits)             | 500 (0-1000 Adjustable) |
| Contrast Ratio                | 7000:1                  |
| Maintanance                   | Front Access            |
| IP Rating                     | IP50                    |
| Max Power Consumption (W/sqm) | ≤650                    |
| Avg Power Consumption (W/sqm) | ≤150                    |
| Viewing Angle                 | 160°                    |
| Refresh Rate (Hz)             | 3840                    |
| Operating Enviroment          | From -10° to 40°        |
| Life Span                     | ≥100,000 Hours          |

### Display Dimensions

